

Overview

Available Lengths	1, 2, 3, 5, 8 m (3.3, 6.6, 9.8, 16.4, 26.3 ft)
-------------------	---

Available Colors	White, Black
------------------	--------------

Pack Options	Single Unit
--------------	-------------

Supported Data Rate	GbE
---------------------	-----

Supported PoE Type	Up to PoE+++
--------------------	--------------

Connector	(2) Shielding RJ45
-----------	--------------------

Operating Environment	Outdoor
-----------------------	---------

Cable

Jacket Diameter	6.3 mm (0.25")
-----------------	----------------

Jacket Material	Thermoplastic elastomer (TPE)
-----------------	-------------------------------

Shielding Type	S/FTP
----------------	-------

Conductor Type	Stranded copper
----------------	-----------------

Conductor Wire Gage	24 AWG
---------------------	--------

Bend Radius	Min. 50.4 mm (1.98")
-------------	----------------------

UV Resistance	ASTM G 151/154
---------------	----------------

Flame Rating	VW-1 (UL1581)
--------------	---------------

Standards	TIA/EIA-568-B.2 ISO/IEC 11801
-----------	----------------------------------

Installation Temperature	-20 to 60°C (-4 to 140°F)
--------------------------	---------------------------

Ambient Storage Temperature	-40 to 80°C (-40 to 176°F)
-----------------------------	----------------------------

Ambient Operating Temperature	-30 to 75°C (-22 to 167°F)
-------------------------------	----------------------------